



Table of content

MASTER LEDtube HF T5

• MASTER LEDtube HF InstantFit T5 HO - 1200 mm	2
• MASTER LEDtube HF InstantFit T5 HO - 1500 mm	3
• MASTER LEDtube HF InstantFit T5 UO - 1500 mm	5
• MASTER LEDtube HF InstantFit HE T5 - 600 mm	6
• MASTER LEDtube HF InstantFit HE T5 - 900 mm	7
• MASTER LEDtube HF InstantFit HE T5 - 1200 mm	8
• MASTER LEDtube HF InstantFit HE T5 - 1500 mm	9

MASTER LEDtube HF T8

• MASTER LEDtube HF InstantFit T8 - 600 mm	10
• MASTER LEDtube HF InstantFit T8 - 1200 mm	11
• MASTER LEDtube HF InstantFit T8 - 1500 mm	13
• MASTER LEDtube Universal T8 - 1200 mm	15
• MASTER LEDtube Universal T8 - 1500 mm	17

CorePro LEDtube HF T8

• CorePro LEDtube HF InstantFit T8 - 600 mm	19
• CorePro LEDtube HF InstantFit T8 - 1200 mm	20
• CorePro LEDtube HF InstantFit T8 - 1500 mm	22
• CorePro LEDtube Universal HO - 1200 mm	24
• CorePro LEDtube Universal HO - 1500 mm	26

MASTER LEDtube HF InstantFit T5 HO - 1500 mm



Ballast Compatibility

KEY

	Ballast is compatible
*	Ballast is compatible, light output may differ >10% compared to specifications
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



	Ballast type	10nc / Ref. no.	Lamps on ballast
TRIDIMCATCO	PC 1/49 T5 INDUSTRY	89800456	1
	PC 1/49 T5 PRO Ip	22087917	1
	PC 1x49 T5 PRO Ip	22185153	1
	PC 1x49 T5 TOP Ip	22185163	1
	PC 2/49 T5 INDUSTRY	89800457	2
	PC 2/49 T5 PRO Ip	22087646	2
	PC 2x49 T5 PRO Ip	22185154	2
	PC 2x49 T5 TOP Ip	22185164	2
	PCA 2/49 T5 ECO Ip	22089499	2
	PC 1/14-35/49/80 T5 PRO-M Ip	22176184	1
	PCA 1x35/49/80 T5 ECO Ip	22185096	1
	PCA 1x35/49/80 T5 EXCEL one4all Ip	22185105	1
	PCA 1x49 T5 BASIC Ip	22185082	1
	PCA 2x35/49 T5 EXCEL one4all Ip	22185106	2
	PCA 2x49 T5 BASIC Ip	22185083	2
	PCA 2x35/49 T5 ECO Ip	22185097	2
VOSSLOH-SCHWABE	ELXd 249.614	188343	2
	ELXc 154.633	188946	1
	ELXc 180.634	188947	1
	ELXd 180.613	188342	1
	ELXd 180.605	188334	1
	ELXc 149.234	183116	1
	ELXc 254.636	188949	2
	ELXc 280.637	188950	2
	ELXd 249.606	188335	2
	ELXd 280.631	188605	2
	ELXc 249.235	183117	2
	ELXd 280.630	188604	2
BAG-HUECO	BCS49.1FX-11/220-240	10077583	1
	BCS49.2FX-11/220-240	10077584	2
	MLD54.1FR-11/220-240/DALI	10097815	1
	BCD49.1F-01/220-240	10097247	1
	MLS80.1/54.2FR-11/220-240	10071609	1
	MLS80.1FR-11/220-240	10071608	1
	MLD80.1FR-11/220-240/DALI	10097820	1
	SCS49.1F-01/220-240	0	1
	MLD54.2FR-11/220-240/DALI	10092121	2
	BCD49.2F-01/220-240	10097297	2
	MLD80.2FR-11/220-240/DALI	10101905	2
	MLS54.2F-01/220-240	166412	2
	MLS80.1/54.2FR-11/220-240	10071609	2
Others	BTLT 149	137998/149	1
	BTLT 249	137999/49	2
	Direct mains		

MAS LEDtube HF 1500mm
HO 26W 8xx T5

Model number / EOC code:
9290012961A / 871869668552500
9290012962A / 871869668554900
9290012963A / 871869668556300

AC (50 Hz) on HF Ballast Compatible

General note Philips Master LEDtube HF InstantFit T5 HO

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips LEDtubes InstantFit T5 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes InstantFit T5 on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips LEDtubes InstantFit T5 range is designed to work on HF ballasts only. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Ballast types indicated in this list with DIM are conditional released by Philips to offer dimming functionality. Please note that the dimming curve of the LEDtube might differ from the curve of a fluorescent lamp. All other Philips LED tubes are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non dimmable product in a dimmable application, warranty does not apply.

MASTER LEDtube HF InstantFit HE T5 - 900 mm

Ballast Compatibility



KEY

	Ballast is compatible
*	Ballast is compatible, light output may differ >10% compared to specifications
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



	Ballast type	12nc	Lamps on ballast
PHILIPS	HF-P 114-35 TL5 HE III IDC 4CIC	9137130310	1
	HF-P 114-35 TL5 HE III IDC C2E	9137130310	1
	HF-P 2 14-35 TL5 HE III IDC	9137130311	2
	HF-S 114-35 TL5 II	9137130429	1
	HF-S 2 14-35 TL5 HE II	9137130421	2
OSRAM	QT-FIT5 1x14-35		1
	QT-FIT5 2x14-35		2
	QTP5 1x14-35		1
	QTP5 2x14-35		2
HELVAR	EL1x14-35ngn5		1
TRIDOMIC ATCO	PC 1-14-35 T5 PRO Ip	22185147	1
	PC 1-14-35 T5 TOP Ip	22185157	1
	PC 2-14-28 T5 TOP Ip	22185158	2
VOSSLOH- SCHWABE			
BAG- HUECO			
Others	Direct Mains		1

MAS LEDtube HF 900mm
HE 11W 8xx T5

Model number / EOC code:
9290019957 / 871869963281600
9290019958 / 871869963283000
9290019959 / 871869963285400

AC (50 Hz) on HF Ballast Compatible

General note Philips Master LEDtube HF InstantFit HE T5

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips LEDtubes InstantFit T5 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes InstantFit T5 on HF ballasts with DC operation is not tested and is therefore not guaranteed.

Philips LEDtubes InstantFit T5 range is designed to work on HF ballasts only. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with ballasts not mentioned in this list, or when using successor models of the tested ballasts.

Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Ballast types indicated in this list with DIM are conditional released by Philips to offer dimming functionality. Please note that the dimming curve of the LEDtube might differ from the curve of a fluorescent lamp. All other Philips LED tubes are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non dimmable product in a dimmable application, warranty does not apply.

MASTER LEDtube HF InstantFit T8 - 1200 mm

Ballast Compatibility



KEY

	Ballast is compatible
*	Ballast is compatible, light output may differ >10% compared to specifications
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



				MASTER LEDtube HF 1200mm 16.5W 833 T8 MEAT	MASTER LEDtube 1200mm HF HO, InstantFit 2100lm	MASTER LEDtube 1200mm HF UO, InstantFit 2500lm
				Model number / EOC code: 9290012263 / 871869656616900	Model number / EOC code: 9290012843A / 871869668752900 9290012841A / 871869668748200 9290012842A / 871869668750500	Model number / EOC code: 9290013002A / 871869668800700 9290013000A / 871869668796300 9290013001A / 871869668798700
				AC (50 Hz) on HF Ballast Compatible	AC (50 Hz) on HF Ballast Compatible	AC (50 Hz) on HF Ballast Compatible
PHILIPS	Ballast type	10nc / Ref. no.	Lamps on ballast			
	EB-C 136 TLD 220-240	9137131992	1			
	HF-B 136 TLD 220-240	9137001122	1		*	*
	HF-B 136 TLD EII 220-240	9137001926	1		*	*
	HF-B 236 TLD 220-240	9137001124	2		*	*
	HF-B 236 TLD EII 220-240	9137001928	2		*	*
	HF-E 136 TLD-D II	9137130410	1			
	HF-E 236 TLD-D	9137130391	2			
	HF-E 236 TLD-D II	9137130411	2			
	HF-K 136 TLD 220-240	9137001477	1		*	*
	HF-P 136 TLD-D III IDC	9137130315	1			
	4CIC / C2E					
	HF-P 236 TLD-D III IDC	9137130316	2			
	4CIC / C2E					
	HF-P 336 TLD-D III IDC	9137130317	3		*	*
	HF-P Xt 136 TLD EII 220-240	9137006177	1		*	*
	HF-P XT 236 TLD EII 220-240	9137006178	2		*	*
	HF-P 136 TLD EII 220-240	9137001911	1		*	*
	HF-P 236 TLD 230-240	9137001112	2			*
	HF-Pi 1 14/21/24/39 TL5 EII 220-240	9137006240	1			
	HF-R 136 TLD-D EII	9137006092	1			
	HF-R 236 TLD-D EII	9137006093	2		Dim	Dim
	HF-R 136 TLD-D 220-240V 50/60Hz	9137001117	1			
	HF-Ri TD 1 14/21/24/39TL5 E+	9137006983	1			
	HF-Ri TD 2 14/21/24/39TL5 E+	9137006984	2			
	HF-S 136 TLD-D II	9137130321	1		*	*
	4CIC / C2E					
	HF-S 236 TLD-D II	9137130324	2			
	HF-S 336 TLD-D II	9137130327	3		*	*
OSRAM	HF-P 118/136 TLD-D III	9137130315	1		*	*
	HF-S 118/136 TLD-D II	9137130321	1		*	*
	HF-P 218/236 TLD-D III	9137130316	2			
	HF-S 218/236 TLD-D II	9137130324	2			
	QT-FIT8 1x36		1		*	*
	QT-FIT8 2x36		2		*	*
OSRAM	QTP8 1x36		1		*	*
	QTP8 2x36		2		*	*
	QTP-OPTIMAL 1x18-40		1		*	*
	QTP-OPTIMAL 2x18-40		2		*	*
	QT-FIT 5/8 2x18-39		2		*	*
HELMAR	EL1x36/40/18S		1		*	*
	EL1x36HF		1		*	*
	EL1x36ngn		1		*	*
	EL2x36/40s		2		*	*
	EL2x36ngn		2		*	*

MASTER LEDtube HF InstantFit T8 - 1200 mm

Ballast Compatibility



KEY

	Ballast is compatible
*	Ballast is compatible, light output may differ >10% compared to specifications
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



			MASTER LEDtube HF 1200mm 16.5W 833 T8 MEAT	MASTER LEDtube 1200mm HF HO, InstantFit 2100lm	MASTER LEDtube 1200mm HF UO, InstantFit 2500lm
			Model number / EOC code: 9290012263 / 871869656616900	Model number / EOC code: 9290012843A / 871869668752900 9290012841A / 871869668748200 9290012842A / 871869668750500	Model number / EOC code: 9290013002A / 871869668800700 9290013000A / 871869668796300 9290013001A / 871869668798700
			AC (50 Hz) on HF Ballast Compatible	AC (50 Hz) on HF Ballast Compatible	AC (50 Hz) on HF Ballast Compatible
Ballast type	10nc / Ref. no.	Lamps on ballast			
TRIDIMC-ATCO	PC 1/36 T8 INDUSTRY	86458035	1		
	PC 1/36 T8 PRO	22176217	1		
	PC 1x36 T8 PRO lp	22185214	1		
	PC2/36 T8 INDUSTRY	86458036	2		
	PC2x36 T8 PRO sl	22185217	2	*	*
	PC 2x36 T8 TOP sl	22185226	2	*	*
	PC 1x36 T8 TOP sl	22185223	1	*	*
	PC1/36 T8 PRO sc	89800008	1		
	PC 1/36 T8 PRO	22176108	1		
	PC 3/36 T8 PRO	22176231	3	*	*
VOSSLOH-SCHWABE	ELXc 136.207	188708	1	*	*
	ELXc 236.202	188316	2	*	*
	ELXc 236.208	188705	2	*	*
	ELXe 238.527	188137	2		
	ELXe 238.527	188137	1		
BAG-HUECO	BCS36.1FX-11/220-240	10077590	1		
	BCS36.2FX-11/220-240	10077591	2		
	D36.2-23021 E	166132	2	*	*
	D 58.1-23021 E	166072	1	*	*
	ECS36.2SR-01/220-240	167032	2		
Tillux	D36.2-23021 E		2		
	D58.1-23021 E		1	*	*
	DD58.1-23031 E		1		
Others	EM ballast		1		
	Direct Mains		1		

General note Philips Master LEDtube HF InstantFit T8

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips LEDtubes InstantFit T8 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes InstantFit T8 on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips LED tube InstantFit range is designed to work on HF ballasts only. For EM ballasts or direct mains connection, please contact a Philips sales representative for more information on our EM/Mains compatible range. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Ballast types indicated in this list with DIM are conditional released by Philips to offer dimming functionality. Please note that the dimming curve of the LEDtube might differ from the curve of a fluorescent lamp. All other Philips LED tubes are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non dimmable product in a dimmable application, warranty does not apply.

MASTER LEDtube HF InstantFit T8 - 1500 mm

Ballast Compatibility



KEY

	Ballast is compatible
*	Ballast is compatible, light output may differ >10% compared to specifications
Dim	Ballast is compatible and conditional released for dimming
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



	Ballast type	10nc / Ref. no.	Lamps on ballast
VOSSLOH-SCHWABE	ELXc 158.201	188315	1
	ELXc 158.209	188706	1
	ELXc 158.218	188870	1
	ELXc 258.203	188317	2
	ELXc 258.210	188707	2
	ELXc 258.219	188871	2
	ELXe 258.222	188130	2
	ELXe 258.222	188130	1
BAG-HUECO	ELXe 158.524	188024	1
	BCD58.1F-01/220-240/1-10V	1009 7145	1
	BCS58.1FX-11/220-240	1007 7592	1
	BCS58.2FX-11/220-240	1007 7593	2
	BCS58.2SX-01/220-240	1005 1003	2
	D 58.1-23021 E	166 072	1
	D 58.2-23021 E	166 082	2
Trilux	SCS58.2SR-11/220-240	166 272	2
	D58.1-23021E		1
May + Christie	DD58.1-23031E		1
	MCU 158		1
Others	MCU 258		2
	Direct mains		
	Electro Magnetic Ballast		

MASTER LEDtube 1500mm HF HO, InstantFit 3100lm	MASTER LEDtube 1500mm HF UO, InstantFit 3700lm
Model number / EOC code: 9290012846A / 871869668758100 9290012844A / 871869668754300 9290012845A / 871869668756700	Model number / EOC code: 9290013005A / 871869668806900 9290013003A / 871869668802100 9290013004A / 871869668804500
AC (50 Hz) on HF Ballast Compatible	AC (50 Hz) on HF Ballast Compatible
*	*
*	*
Dim / *	Dim / *
*	*
*	*

General note Philips Master LEDtube HF InstantFit T8

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips LEDtubes InstantFit T8 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes InstantFit T8 on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips LED tube InstantFit range is designed to work on HF ballasts only. For EM ballasts or direct mains connection, please contact a Philips sales representative for more information on our EM/Mains compatible range. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Ballast types indicated in this list with DIM are conditional released by Philips to offer dimming functionality. Please note that the dimming curve of the LEDtube might differ from the curve of a fluorescent lamp. All other Philips LED tubes are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non dimmable product in a dimmable application, warranty does not apply.

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions

MASTER LEDtube Universal T8 - 1200 mm

Ballast Compatibility



KEY

	Ballast is compatible
*	Ballast is compatible, light output may differ >10% compared to specifications
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



	Ballast type	10nc	Lamps on ballast
VOSSLOH-SCHWABE	ELXc 136.207	188708	1
	ELXc 236.202	188316	2
	ELXc 236.208	188705	2
	ELXe 238.527	188137	2
	ELXe 238.527	188137	1
BAG-HUECO	BCS36.1FX-11/220-240	10077590	1
	BCS36.2FX-11/220-240	10077591	2
	D36.2-23021 E	166132	2
	D 58.1-23021 E	166072	1
	ECS36.2SR-01/220-240	167032	2
Tritlux	D36.2-23021 E		2
	D58.1-23021E		1
	DD58.1-23031E		1
Others	EM ballast		1
	Direct Mains (only one single side supply)		1

MASTER LEDtube 1200mm Universal, Instant Fit 2500lm
Model number / EOC code: 9290013361 / 871869670537700 9290013362 / 871869670539100 9290013360 / 871869672853600
AC (50Hz) on HF Ballast Compatible
*
*
*
*

General note Philips Master LEDtube Universal T8

General notes: Philips LEDtubes Universal T8 are designed to work on HF ballasts, or EM ballast, or direct mains connection.

For HF ballast connection: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

Please note that Philips LEDtubes Universal T8 are only tested with HF ballast on AC operation. The performance of Philips LEDtubes Universal T8 on HF ballasts with DC operation is not tested and is therefore not guaranteed. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with HF ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

For EM ballasts or direct mains connection: Please refer to the installation guide.

MASTER LEDtube Universal T8 – 1500 mm

Ballast Compatibility



KEY

	Ballast is compatible
*	Ballast is compatible, light output may differ >10% compared to specifications
	Ballast is not compatible
	Ballast LEDtube combination not tested

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



	Ballast type	10nc / Ref. no.	Lamps on ballast
PHILIPS	EI 158 TLD 220-240	9137 006 075	1
	HF-B 158 TLD 220-240	9137 001 123	1
	HF-B 158 TLD EI 220-240	9137 001 927	1
	HF-B 258 TLD 220-240	9137 001 125	2
	HF-B 258 TLD-D EI 220-240	9137 001 929	2
	HF-E 158 TLD-D	9137 130 389	1
	HF-E 1/2 58 TLD-D II	9137 130 409	2
	HF-E 1/2 58 TLD-D II	9137 130 409	1
	HF-P 154/155 TLD HO/PL-L III IDC	9137 130 282	1
	HF-P 158 TLD EI 220-240	9137 001 912	1
	HF-P 158 TLD-D III IDC	9137 130 318	1
	HF-P 258 TLD EI 220-240	9137 001 916	2
	HF-P 258 TLD-D III IDC	9137 130 319	2
	HF-P Xt 158 TLD EI 220-240	9137 006 179	1
	HF-P Xt 258 TLD-D EI 220-240	9137 006 180	2
	HF-P 158 TLD 220-240	9137 001 185	1
	HF-P 258 TLD 220-240	9137 001 110	2
	HF-R 158 TLD 220-240	9137 001 118	1
	HF-R 258 TLD 220-240	9137 001 119	2
	HF-R 158 TLD EI	9137 006 094	1
	HF-R 258 TLD EI	9137 006 095	2
	HF-R TD 258 TLD EI 220-240	9137 006 070	2
	HF-RITD 1 28/35/49/54TL5 E+	9137006956	1
	HF-RITD 2 28/35/49/54TL5 E+	9137006958	2
	HF-S 158		1
	HF-S 158 TLD-D II	9137 130 322	1
	HF-S 158 TLD-D II 220-240V 50/60Hz	9137 130 322	1
	HF-S 258 TLD-D II	9137 130 325	2
	HF-S 258 TLD-D II HT	9137 006 899	2
	HF-S 158 TLD 220-240	9137 006 319	1
	EB-P 258 TLD ICC 220-240	9137 130 210	2
	OSRAM	QT Deluxe HF 1x58 230-240 DIM	
QT Deluxe HF 2x58 230-240 Dim			2
QT-FIT8 1x58 - 70			1
QT-FIT8 2x58 870			2
QTP8 1x58			1
QTP8 2x58			2
QTP-OPTIMAL 1x54-58			1
QTP-OPTIMAL 2x54 858			2
QT 1X58 DIM			1
QT-FIT 5/8 1x54-58			1
QT-FIT 5/8 2x54-58		2	
HELVAR	EL1x58ngn		1
	EL1x58s		1
	EL2x58es		2
	EL2x58HF		2
	EL2x58ngn		2
EL2x58s		2	
TRIDONE ATCO	PC 1/58 T8 INDUSTRY	86 458 037	1
	PC 1/58 T8 PRO	22 176 094	1
	PC 1x58 T8 PRO Ip	22 185 215	1
	PC 2/58 T8 INDUSTRY	86 458 038	2
	PC 2x58 E011		2
	PC 2x58 E011 IDC	22 083 174	2
	PC 2x58 T8 PRO sl	22 185 218	2
	PC 1x58 T8 TOP sl	22185224	1
	PC 2x58 T8 TOP sl	22185227	2
	PCA 1/58 excel one4all	22 085 286	1
PCA 2x58 EXCEL One4all Ip	28 000 040	2	

[illegible]

	Ballast is compatible
•	Ballast is compatible, light output may differ >10% compared to specifications
	Ballast is not compatible

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



	Ballast type	10nc / Ref. no.	Lamps on ballast
VOSSLOH-SCHWABE	ELXc 136.207	188708	1
	ELXc 236.202	188316	2
	ELXc 236.208	188705	2
	ELXe 238.527	188137	2
BAG-HUECO	BCS36.1FX-11/220-240	10077590	1
	BCS36.2FX-11/220-240	10077591	2
	D36.2-23021 E	166132	2
	D 58.1-23021 E	166072	1
	ECS36.2SR-01/220-240	167032	2
Tillix	D58.1-23021E		1
	DD58.1-23031E		1
Others	EM ballast		1
	Direct Mains		1

[illegible]

General notes: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list. Please note that Philips LEDtubes are only tested with HF ballast on AC operation. The performance of Philips LEDtubes on HF ballasts with DC operation is not tested and is therefore not guaranteed. Philips LED tube InstantFit range is designed to work on HF ballasts only. For EM ballasts or direct mains connection, please contact a Philips sales representative for more information on our EM/Mains compatible range. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDtubes with ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDtube. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Philips CorePro LEDtubes HF InstantFit T8 are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.



KEY

Ballast is compatible
• Ballast is compatible, light output may differ >10% compared to specifications
Ballast is not compatible

This document is for information purposes and must be treated as recommendation. Philips attempted to provide best results, results are generated in lab controlled environment and may differ from actual application conditions



	Ballast type	10nc / Ref. no.	Lamps on ballast
VOSSLOH-SCHWABE	ELXc 136.207	188708	1
	ELXc 236.202	188316	2
	ELXc 236.208	188705	2
	ELXe 238.527	188137	2
	ELXe 238.527	188137	1
BAG-HUECO	BCS36.1FX-11/220-240	10077590	1
	BCS36.2FX-11/220-240	10077591	2
	D36.2-23021 E	166132	2
	D 58.1-23021 E	166072	1
	ECS36.2SR-01/220-240	167032	2
Tillux	D36.2-23021 E		2
	D58.1-23021E		1
	DD58.1-23031E		1
Others	EM ballast		1
	Direct Mains (only one single side supply)		1

CorePro LEDtube UN 1200mm HO 18W8xx T8
Model number / EOC code: 9290018692 / 871869680166600 9290018693 / 871869680168000 9290018694 / 871869680170300
AC (50Hz) on HF Ballast Compatible

General note Philips CorePro LEDtube Universal HO

General notes: Philips LEDtubes Universal T8 are designed to work on HF ballasts, or EM ballast, or direct mains connection.

For HF ballast connection: Refer to the product reference number in the header of the columns to use this product-ballast compatibility list.

FOR HF ballast connection: Refer to the product reference number in the header on the columns to use this product-ballast compatibility list.

Please note that Philips LEDTubes Universal T8 are only tested with HF ballast on AC operation. The performance of Philips LEDTubes Universal T8 on HF ballasts with DC operation is not tested and is therefore not guaranteed. This document is for information purposes only and must be treated as recommendation. Philips will not accept claims for any damage caused by not implementing the recommendations in this document. Philips does not accept any responsibility, warranty or liability when using Philips LEDTubes with HF ballasts not mentioned in this list, or when using successor models of the tested ballasts. Although Philips aims to provide the most accurate information and test results from controlled experiments the results may vary in different applications. This document focuses on the behaviour of above mentioned Philips LEDTubes. Please also check and follow the instructions of HF ballast manufacturers for installation instructions.

Always check the latest update of the compatibility list on www.philips.com/ledtube

Dimming a LEDtube: Philips CorePro LEDtubes Universal HO are not developed for dimming therefore the performance cannot be guaranteed in a dimming application. In case of usage of a non-dimmable product in a dimmable application, warranty does not apply.

For EM ballasts or direct mains connection: Please refer to the installation guide



© 2019 Signify Holding. All rights reserved. The information provided herein is subject to change, without notice. Signify does not give any representation or warranty as to the accuracy or completeness of the information included herein and shall not be liable for any action in reliance thereon. The information presented in this document is not intended as any commercial offer and does not form part of any quotation or contract, unless otherwise agreed by Signify.

Philips and the Philips Shield Emblem are registered trademarks of Koninklijke Philips N.V. All other trademarks are owned by Signify Holding or their respective owners.

09/2019
Data subject to change.

www.philips.com/LEDtube